

IN THE CLAIMS:

Amendments to the Claims:

Please amend claims 1-5 as shown below.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A flat panel display device comprising:

a first panel having a plurality of electron beam sources which are arranged in a matrix array, the electron beam sources being constituted of cathodes which emit electrons and control electrodes which are electrically insulated from the cathodes and control ~~a~~the quantity of electrons emitted from the cathodes, and a plurality of cathode lines and a plurality of control electrode lines which, in a state ~~that~~in which the cathodes and the control electrodes which constitute respective electron beam sources are respectively separated into a plurality of sets, electrically connect the cathodes and the control electrodes for the respective sets, ~~and making the electron beam sources designated by respectively selecting some of the cathode lines and the control electrode lines~~ serving to emit electrons, and

a second panel having phosphors which emit light when impinged upon ~~receiving the~~by electrons emitted from the electron beam sources corresponding to the arrangement of the electron beam sources, wherein

the cathodes and the control electrodes are arranged on the first panel ~~such that out of a~~in a first flat cross-sectional plane which is parallel to the second panel,

~~a cross-sectional plane which is brought into contact with the cathodes and the control electrodes is present and, further, a~~ the control electrode lines are arranged in a second cross-sectional plane which includes the control electrode lines differs from and is spaced from the first cross-sectional plane which is brought into in contact with the cathodes and the control electrodes.

2. (currently amended) A flat panel display device according to claim 1, wherein on a straight line which connects an arbitrary point on ~~the~~ a cathode and a point in ~~an~~ a portion of ~~the~~ a control electrode closest to the point on the cathode, an insulation material is present.

3. (currently amended) A flat panel display device according to claim 1, wherein the flat panel display device includes partition walls each of which has one end thereof ~~brought into in~~ contact with a second-panel-side surface of the control electrode and another end thereof ~~erected~~ extending in ~~the~~ a direction toward the second panel.

4. (currently amended) A flat panel display device according to claim 3, wherein portions of surfaces of the partition walls include conductive films having a lower ~~electric~~ electrical resistance than other portions on the surfaces of the partition walls, and the plurality of control electrodes are electrically connected to each other through the conductive films.

5. (currently amended) A flat panel display device according to claim 3,

wherein at least portions of ~~another~~ said other ends of the partition walls are brought ~~into~~ in contact with the second panel and ~~the~~ conductivity is established between the portions which are brought ~~into~~ in contact with the second panel and said one ends of the partition walls which are brought ~~into~~ in contact with the control electrodes.

6. (original) A flat panel display device according to claim 1, wherein the cathodes include an electron emission material which directly emits electrons in a vacuum and the electron emission material contains carbon as a main component.

7. (original) A flat panel display device according to claim 6, wherein the main component of the electron emission material is one selected from a group consisting of carbon nanotubes, micro carbon fibers, diamond, diamond-like carbon.